

Advice to use integrated dust evacuation, in case of air recirculation in accordance to EN 60335.
 Recommendation to use respiratory protection equipment when sanding, even in combination with integrated dust evacuation.
 Advice to use local exhaust ventilation according to EN 15012 for welding of coated substrates.
 Advice to provide spill retention system according to applicable regulation.
 Recommendation to avoid contact with water.

Standardised use descriptors according European Chemical Agency (EChA) Guidance on information requirements and chemical safety assessment, chapter R.12

SU3	Industrielle anvendelser: Anvendelser af stoffer som sådan eller i kemiske produkter på industri-anlæg
SU 22	Faglige anvendelser: Det offentlige område (administration, uddannelse, forlystelser, tjeneste-ydelser, håndværkere)
PC9a	Belægninger og maling, fortyndere, farvefjernere
PC9b	Fyldstoffer, kit, puds, modellervoks
PROC2	Anvendelse i lukket, kontinuerlig proces med kontrolleret lejlighedsvis eksponering
PROC3	Anvendelse i lukket batchproces (syntese eller formulering)
PROC4	Anvendelse i batch- eller anden proces (syntese) med mulighed for eksponering
PROC5	Blanding eller iblanding i batchprocesser til formulering af kemiske produkter og artikler (flere stadier og/ eller betydelig kontakt)
PROC7	Industriel sprøjtning
PROC8a	Overførsel af stof eller kemisk produkt (påfyldning/ udtømning) fra/ til kar/ store beholdere på ikke-dedikerede anlæg
PROC8b	Overførsel af stof eller kemisk produkt (påfyldning/ tømning) fra/ til kar/ store beholdere på dedikerede anlæg
PROC11	Ikke-industriel sprøjtning
PROC24	(Mekanisk) højenergibearbejdning af stoffer bundet i materialer og/ eller artikler
ERC4	Industriel anvendelse i pro-cesser og produkter af pro-cesshjælpemidler, der ikke bliver en del af artikler
ERC5	Industriel anvendelse, der medfører, at stoffet indgår i eller påføres på en grund-substans
ERC12a	Industriel bearbejdning af artikler ved slibeprocesser (lav frigivelse)
ERC6d	Industriel anvendelse af procesregulerende midler ved produktion af kunstharpiks, gummi og polymerer

Glossary

SU	Anvendelsessektor
PC	Produktkategori
PROC	Proceskategori
ERC	Miljøudledningskategori
AC	Artikkelkategori
spERC	Sector specific environmental release category (for ACEA uses)
ACEA	European automobile manufacturers association
AIRC	Federation of vehicle repair organisations
CEPE	European council of producers and importers of paints, printing inks and artists' colours
OC	Operational condition
DOA	Duration of activity
LEV	Local exhaust ventilation
TRV	Technical room ventilation
RMM	Risikohåndteringsforanstaltninger
RPE	Respiratory protection equipment
DPE	Dermal protection equipment
WWTP	Waste water treatment plant (on-site)
STP	Sewage treatment plant (municipal)
SVHC	Substance of very high concern
LSI	Lead substance indicator
M(sperc)	Maximum volume of lead substance which can be used safely under conditions described by CEPE spERC
DNEL	Afledte nuleffektniveauer
DMEL	Derived minimum effect level
PNEC	Beregnet nuleffekt-koncentration
ECETOC TRA	Targeted risk assessment as proposed by European center for ecotoxicology and toxicology of chemicals
RCR	Risk characterisation ratio